



TYPE	0.5	1.0	2.0	4.0	6.0	8.0	13	16	19
TORQUE(kg·m)	0.55	1.1	2.2	4.5	7	7	14	17.5	20
CAPACITY(W, 20°C)	11	15	20	25	30	35	40	45	55
GAP	0.3	0.3	0.3	0.5	0.5	0.5	0.5	0.5	0.5
HUB dH7	12	15	20	25	30	30	30	40	40
KEY bE9 X h	4X13.8	5X17.3	5X22.3	7X28.3	7X33.3	7X33.3	7X33.3	10X43.3	10X43.3
A	63	80	100	125	137	160	180	200	216
B	68	85	106	133	146	169	190	213	229
C	46	60	76	95	105	120	147	158	176
D	80	100	125	150	165	190	210	230	270
E	72	90	112	137	150	175	195	215	245
F	35	42	52	62	65	80	106	100	130
G	34	41	51	61	64	79	106	100	125
H	21	24	27	30	32.5	34	38	40	50
I	2	2	3	4	4	4	5	5	6
J	4	5	6	7.5	9.5	9.5	12	12	14
K	24	27	30	33	35	37	42	44	55
L	28.6	31.8	36.8	40.2	43.1	46.9	53	56	67.9
M	3.1	4.1	5.1	6.1	8.1	8.1	10.2	10.2	12.2
N	8	10	12	13	18	18	20	20	23
Q	4.5	5.5	6.5	6.5	65	8.5	9.5	9.5	10.5
T	8	12	12	13	18	18	20	20	20

Example

