



TYPE	0.5	1.0	2.0	4.0	6.0	8.0	13	16	19
TORQUE(kg-m)	0.55	1.1	2.2	4.5	7	7	14	17.5	20
CAPACITY(W, 20°C)	11	15	20	25	30	35	40	45	55
GAP	0.3	0.3	0.3	0.5	0.5	0.5	0.5	0.5	0.5
HUB dH7	12	15	20	25	30	30	30	40	40
KEY bE9 X h	4X13.8	5X17.3	5X22.3	7X28.3	7X33.3	7X33.3	7X33.3	10X43.3	10X43.3
A	63	80	100	125	160	160	180	200	216
B	68	85	106	133	169	169	190	213	229
D	80	100	125	150	190	190	210	230	270
E	72	90	112	137	175	175	195	215	245
F	35	42	52	62	80	80	106	100	130
G	38	45	55	64	75	75	88	90	104
H	22	24	27	30	33	33	38	40	50
I	2	2	3	4	4	4	5	5	6
K	24	27	30	33	37	37	42	44	55
L	53.3	62.8	73.3	89	107	107	121.5	128.5	147.5
M	20	25	30	40	50	50	55	60	65
N	33	40	47	52	62	62	74	75	92
Q	4.5	5.5	6.5	6.5	8.5	8.5	9.5	9.5	10.5
R	3-M4	3-M4	4-M4	4-M4	4-M5	4-M5	4-M6	4-M6	4-M8
W X U	4X39.5	5X47	5X57	7X67	7X78	7X78	7X91	10X93	10X107

Example

