



TYPE	0.5	1.0	2.0	4.0	6.0	8.0	13	16	19
TORQUE(kg-m)	0.55	1.1	2.2	4.5	7	7	14	17.5	20
CAPACITY(W, 20°C)	11	15	20	25	30	35	40	45	55
GAP	0.3	0.3	0.3	0.5	0.5	0.5	0.5	0.5	0.5
HUB dH7	12	15	20	25	30	30	30	40	40
KEY bE9 X h	4X13.8	5X17.3	5X22.3	7X28.3	7X33.3	7X33.3	7X33.3	10X43.3	10X43.3
A	63	80	100	125	137	160	180	200	216
B	68	85	106	133	146	169	190	213	229
C	46	60	76	95	105	120	147	158	176
E1	43	55	60	78	88	101	109	128	138
E2	7	8	8	10	10	11	11	12	12
G	34	41	51	61	64	79	106	100	130
H	28	30	34	38	40	44	60	60	60
I	1.5	2	3	4	4	4	4	6	6
J	4	5	6	7.5	9.5	9.5	12	12	14
K	24	26.5	30	33.5	34.5	39	49	49	49
L	23.6	34.8	40.3	45.2	48.2	53.9	72	72	72.9
M	3.1	4.1	5.1	6.1	8.1	8.1	10.2	10.2	12.2
N	8	10	12	13	18	18	20	20	23
S1	5	7	9	9	11	11	13	13	13
S2	15	16	20	22	25	30	30	30	40
T	8	12	12	13	18	18	20	20	20

Example

