



TYPE	4.0	8.0	13	16	20	40	70	100	150	200
GAP	0.3	0.5	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6
HUB dH7	25	30	30	40	40	45	50	55	60	75
KEY bE9 X h	7X28	7X33	7X33	10X43.3	10X43.3	12X48.3	12X53.5	12X58.3	18X64.4	20X79.9
TORQUE(kg·m)	4.0	8.0	13	16	20	40	70	100	150	200
CAPACITY(W, 20°C)	24	24	24	24	24	24	24	90	90	90
A	128	160	180	200	216	260	320	400	480	550
G	41	65	65	65	66	85	80	120	130	140
E	56	68	83	85	108	156	200	248	310	400
F(H8)	45	50	65	70	89	136	180	228	280	380
K	26	30	30	32	36	37	48	45	50	50
Q	6- $\phi$ 6.5	6- $\phi$ 6.5	6- $\phi$ 6.5	6- $\phi$ 9	6- $\phi$ 9	8- $\phi$ 9	8- $\phi$ 11	8- $\phi$ 11	10- $\phi$ 11	12- $\phi$ 11
L	70	76.5	88.5	87.5	96.5	93.6	118.6	120.6	127.6	127.6